

THE PUP LP-550

Tired of handwrapping?

Shipping just a few pallets a day?

Worried about your personnel because of safety concerns associated with handwrapping?

The PUP is the perfect answer to your medium-duty low volume application

Designed with non-proprietary parts that can be purchased locally and includes a strong 3/5 year warranty

Friction Brake Film Carriage uses handwrap and machine grade films
Ideal for Pre-Stretched Film and Netting

Variable Spiral Speed Film Carriage
Side Mounted for Operator Safety

THREE MODELS TO CHOOSE FROM:

550-M

Operator controls carriage up/down travel with selector switch throughout the wrap cycle.

550-SA

Includes top/bottom wrap timers and cycle start button so the operator can walk away while the load is being wrapped. The film carriage up travel is controlled by an adjustable limit switch that the operator needs to position properly prior to initiating cycle start.

550-SAP

Same as the 550-SA semi-automatic model except it includes the automatic load height sensor (photo-eye) that controls the film carriage up travel by automatically finding the top of the load and stopping the carriage in the proper location for pre-selected top wraps.

Variable Speed Turntable 3000# Capacity
Optional Ramp Available for use with Pallet Jacks

Built in North America with Brand Name Components.

The PUP LP-550 has Features & Benefits that Surpass the Competition.

- ❖ Affordable and simple with more standard features than any other pallet wrapper in this price range.
- ❖ A quality machine built with quality components and supported by a local qualified distributor.

We invite you to go online at www.cousinsspackaging.com for more information or call your local distributor.

1 888 209 4344

PUP LP-550 DESIGN FEATURES/SPECIFICATIONS

550 PUP - Medium Duty Low Profile Stretch Wrapper

Power Requirement: 115V/1Ph/60 Hz/10A dedicated service

Maximum Load Size: 48" W x 48" L x 80" H
68" maximum load diagonal

Maximum Load Weight: 3,000lb dynamic/8,000lb static

Turntable

- ❖ 57" diameter $\frac{5}{16}$ " thick laser-cut steel plate
- ❖ **18 point turntable support system**
- ❖ Turntable height 2- $\frac{1}{4}$ " from floor
- ❖ Safety surround ring encloses turntable

Turntable

- ❖ 0 to 9 RPM rotational speed
- ❖ DC variable speed drive motor
- ❖ ANSI #50 direct chain drive

Carriage Elevator

- ❖ DC variable speed motor
- ❖ Belt lift
- ❖ 4 point "V" wheel guidance system

Film Delivery System

- ❖ Manual friction brake tensioning
- ❖ Standard 20" W x 10" Diameter roll (max)

Control Features

- ❖ Simple to operate
- ❖ Power ON/E STOP push/pull button
- ❖ Turntable JOG/RUN selector switch
- ❖ Film carriage LOWER/RAISE selector switch
- ❖ Top and Bottom Wrap Timers (550-SA & SAP only)
- ❖ Turntable Jog/Cycle Start Selector Switch (550-SA & SAP only)
- ❖ Automatic Load Height Sensor Photo-eye (550-SAP only)

Other Features

- ❖ Formed steel base construction
- ❖ Formed sheet metal tower
- ❖ 900lb estimated shipping weight

Warranty

- ❖ 3/5 years

