



MODEL LP 550 "PUP"
MEDIUM DUTY LOW PROFILE TURNTABLE
STRETCH WRAP SYSTEM GENERAL SPECIFICATIONS

PRODUCTION SPEED

- 1-15 loads per hour

NOTE: Process rates will vary with load size; number of wraps & forklift load/unload time

LOAD CAPACITY

- Maximum load weight: 3,000# dynamic – 8,000# static
- Maximum load size: 48" W x 48" L x 75" H (68" max. load diagonal)

NOTE: Maximum load size shown is the largest load the 550 PUP will wrap – no exceptions

TURNTABLE

- 57" diameter laser-cut steel plate
 - 18 point turntable support system
 - Turntable height 2-1/4" from floor
 - ANSI # 50 direct chain drive c/w chain tensioner
 - 1 - 9 RPM rotational speed c/w soft start acceleration
 - 1/4 HP DC variable speed gear-motor
 - Safety surround ring encloses turntable
 - Optional loading ramp 40" long x 60" wide available
-

**FILM CARRIAGE
ELEVATOR**

- 1/8 HP DC variable speed gear-motor
 - Direct flat belt drive system
 - 4 point "V" wheel carriage guidance system with side thrust rollers
-

**FILM DELIVERY
SYSTEM / FILM
CAPACITY**

- Manually adjusted friction brake web tensioning system
 - Side mounted film carriage for operator convenience and safety
 - Accepts hand-wrap to machine grade films, 12" to 20" roll width, up to 10" diameter
-

CONTROL FEATURES**– Manual Model
LP 550-M**

- Simple to operate
- Power On / Emergency Stop button
- Turntable Jog / Run switch
- Film Carriage Lower / Raise switch
- Film carriage variable speed control
- Turntable variable speed control
- Non-proprietary UL/CSA approved components

CONTROL FEATURES**– Semi-Automatic
Models LP 550-SA &
LP 550-SAP**

- Simple to operate
- Power On / Emergency Stop button
- Turntable Jog / Cycle Start switch
- Film Carriage Lower / Raise switch
- Turntable variable speed control
- Film carriage variable speed control
- Separate top & base wrap duration timers
- Adjustable top limit switch wrap height control
- Auto Load Height Sensing photo-eye (on LP 550-SAP model only)
- Non-proprietary UL/CSA approved components

**STRUCTURAL
FEATURES**

- Formed steel base construction
- Formed steel tower
- Forklift truck portable base design – pick-up angles included

**ELECTRICAL INPUT
REQUIREMENTS**

- 115 Volts 1 Phase 60 Hz 10 Amps
-